

## Single Output General Purpose Power Supplies

### Features

- ◆ Low Cost
- ◆ Active Power Factor Correction
- ◆ Universal Input (85 - 265VAC)
- ◆ Input Transient Protected IEC61000-4
- ◆ SEMI F47 Certified (208VAC Input)
- ◆ Global safety Approvals
- ◆ Level B EMI



### Key Market Segments & Applications



Specifications		
Model		SWS300                      SWS600
Input Voltage range (1)	-	85 - 265VAC (47 - 63Hz) or 120 - 370VDC*
Inrush Current (115 / 230VAC)	A	20 / 40 at 25°C, cold start
Power Factor	-	Meets EN61000-3-2
Input Current (100/200VAC)	A	3.6 / 1.8A                      7.2 / 3.6A
Temperature Coefficient	-	<0.02%/°C
Overcurrent Protection	-	>105%, Constant current style
Overvoltage Protection	V	3.3V: 4.1-5.3V, 5V: 6.25-7.5V, 12V: 13.8-16.8V 15V: 19.3-24.2V, 24V: 30-34.8V, 36V: 41.4-50.4V, 48V: 60-69.6V
Overtemperature Protection	-	Yes, cycle AC to reset
Hold Up Time (Typ)	ms	20ms at 115/230VAC
Leakage Current (max)	mA	SWS300: 0.75mA, SWS600: 1.5mA
Remote Sense	-	None                      Yes
Parallel Connection	-	None                      Yes
Remote On/Off	-	None                      Yes, >4.5V to shutdown
Power Fail Signal	-	None                      Yes, open collector output
LED Indicator	-	Green LED = On
Operating Temperature	°C	-10 to +65°C (See table for derating - model specific)
Storage Temperature	°C	-30 to +85°C
Humidity (non-condensing)	-	30 - 90% RH operating, 10 - 95%RH non operating
Cooling	-	Internal fan
Withstand Voltage	-	I/P to Grnd 2kVAC, I/P to O/P 3kVAC, O/P to Grnd 500VAC, O/P to CNT 100VAC for 1 min
Isolation Resistance	-	>100M at 25°C & 70%RH, Output to Ground 500VDC
Vibration (non operating)	-	10 - 55Hz (sweep for 1 min) 19.6m/s <sup>2</sup> constant X, Y, Z 1 hour each plane)
Immunity	-	EN61000-4-2, -3, -4, -5, -6, -8, -11
Safety Agency Approvals	-	UL60950-1, CSA60950-1, EN60950-1, EN50178, CE Mark, SEMI F47 (208VAC)
Conducted & Radiated EMI	-	EN55011 / EN55022-B, FCC Class B
Recommended EMI Filter	-	MC1206                      MC1210
Weight (Typ)	g	950                      2000
Size (WxHxD)	in	2.05 x 4.01 x 7.8"                      3.62 x 4.72 x 7.48"
Warranty	yrs	Two Years

Notes:(1) Derate linearly to 80% load from 115VAC to 85VAC input (derate to 90% load for SWS600-5, no derating SWS300, 600-3)

\*Safety certified for AC input only

# Not Recommended For New Designs

